



STRIKE FIRST
CORPORATION

MANUFACTURING FIRE EQUIPMENT FOR OVER 35 YEARS

WATER

BUILT TOUGH AND EASY TO SERVICE

STRIKE FIRST WATER FIRE EXTINGUISHERS ARE DESIGNED FOR:



WOOD,
PAPER,
CLOTH

CLASS A

- Polished stainless steel cylinder complete with protective skirt
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Colour and bar-coded labels for accurate service
- Shipped without pressure
- Schrader valve for pressurizing



LISTED

MEETS OR EXCEEDS:
ANSI/UL 154 & 711



LISTED
HOMOLOGUÉ

MEETS OR EXCEEDS:
CAN/ULC-S503 & S508

- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- Temperature range: 40°F to 120°F (4°C to 49°C)



The STRIKE FIRST water extinguisher is an ideal choice for Class A fire hazards. The powerful stream of water allows it to reach areas other extinguishers cannot.

An effective extinguisher for class A fires in areas such as warehouse, agriculture and industrial locations.



CAPACITY	2.4 gallons (9 litres)
Model No.	SF-PW250
UL/ULC Rating	2-A
Range	40 ft (12.2 m)
Discharge Time	40 sec
PSI	100
Height	25" (63.5 cm)
Width	8 3/4" (22 cm)
Diameter	7 1/8" (18 cm)
Weight	7.9 lb (3.6 kg)
Standard Bracket	Wall