

# Copper Spray



## High-quality and effective

WEICON Copper Spray is a high-quality, weather-resistant metal spray with high adhesive strength and a high copper content for protective and decorative coatings with an appealing non-ferrous metal character for indoor and outdoor use. It is even used for the optical refinement (copper-plating) of various material surfaces or design parts. Copper Spray can be used on window sills, gutters and downspouts, outdoor lights and mailboxes, as well as for arts and crafts and decorative work.

### Technische Daten

Silicone-free	yes
Application area	indoor and outdoor use
Binder	Acrylate resin
Pigment	copper pigments
Pigment purity	ca. 99.9% Cu
Metal content in dry film	~50 %
Processing temperature	+5 to +35°C, ideally +18 to +35°C
Recommended primer	Zinc Spray
Consumption	120 ml/m <sup>2</sup>
Layer thickness with 1.5 crosswise applications approx.	20 -30 µm
dust-dry	10 min.
cured after	4 h
Cross cutting	DIN 53151/ISO 2409 Cross cutting test value 0 to 1
Cylindrical mandrel bend test	DIN EN ISO 1519 no hairline cracking
Topcoat	not required
Density	0,9 g/cm <sup>3</sup>
Temperature resistance	-50°C to +300°C
Shelf life	24 mon.

### Surface pre-treatment

Clean and degrease surfaces with WEICON Surface Cleaner.

### Processing

Shake can before use, until until the mixing pea is clearly audible. Apply evenly at room temperature (approx. +20°C/+68°F) from a distance of approx. 25 cm in crosswise layers. Dust-dry after 10 min., fully cured after approx. 4-6 hours.

### Storage

Pressurized container. Protect from direct sunlight and temperatures above +50°C.

### Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

### Available sizes:

11101400 Copper Spray, 400 ml

To the product detail page:



#### Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.