

Technische Sprays

Grease Sprays

Adhering Grease extra strong



Adheres even under water

WEICON Adhering Grease extra strong is a special lubricant and corrosion protectant even for underwater applications. It provides effective protection against aggressive fluids in maritime applications and in wet plants. Adhering Grease extra strong is suitable for rolling and sliding bearings even in mixed friction operation, for joints, levers, sliding guides, spindles, spline shafts, exposed gears, worm gears, chains and wire cables. It is suitable for all slide speeds permissible for grease lubrication.

Technische Daten

| Odour | | nearly odourless |
|-------------------------------|------------|--------------------------|
| Colour | | beige |
| Specific properties | | adheres even under water |
| Kinematic viscosity (40 °C) | DIN 51 562 | 100 mm ² /s |
| Kinematic viscosity (+100 °C) | DIN 51 562 | 9 mm²/s |
| Temperature resistance | | -25 to +80 |
| Shelf life | | 24 mon. |
| Approvals / Guidelines | | |
| ISSA Code | | 53.402.52 |

Processing

Clean surfaces. For a better spray function, warm the product up to room temperature. Shake can before use until mixing pea is audible. Spray on from a distance of approx. 15 cm.

Storage

Pressurized container. Protect from direct sunlight and temperatures above +50°C.

Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our safety data sheets (www.weicon.com) must be observed.

Available sizes:

11540400 Adhering Grease extra strong, 400 ml, beige

page:



Vote

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the requested properties are recommended. A claim cannot be derived from them.