Technical Datasheet Create Date: 17.11.2017 - Seite 1/2

Easy-Mix RK-7100 Structural Acrylic Adhesive



fast-curing high strength impact resistant, residual elasticity

WEICON Easy-Mix RK-7100 can be used to bond numerous materials such as plastics, metals and ceramics to themselves and among. It is particularly convenient for structural bondings if high-strength connections are required. The adhesive is very viscous and is therefore suitable also for applications on vertical surfaces.

WEICON Easy-Mix RK-7100 can be used universally and, for example, in plastics technology, metal construction, car body and vehicle construction, machine construction, electrical engineering, model and mould making and in trade show and exhibition construction.

Technical Data

Base	Methyl methacrylate	
Colour after curing	cream white, milky	
Mixing ratio resin/hardener	1:1	
Density of the mixture	0,98 - 1,02 g/cm ³	
Viscosity of the mixture	40.000 - 60.000 mPa⋅s	
Application procedure	Easy-Mix	
Composition	viscous	
Pot-life at +20°C (+68°F)	5 min.	
Handling strength (35% strength) after	25 min.	
Capable of bearing mechanical loads (50% strength) after		
Processing temperature +10		
Curing temperature	+18 °C	

Shear strength according to DIN 53281 at: Aluminium Steel sand blasted Stainless Steel PC PMMA ABS Hard-PVC GRP CRP Polyamide 6.6			•
Shear strength according to DIN 53281 at: Aluminium Steel sand blasted Stainless Steel PC PMMA ABS Hard-PVC GRP CRP Polyamide 6.6	12 h		-inal strength (100%) after
Aluminium Steel sand blasted Stainless Steel PC PMMA ABS Hard-PVC GRP CRP Polyamide 6.6),1 - 5,0 mm	(Adhesive gap bridging
Steel sand blasted Stainless Steel PC PMMA ABS Hard-PVC GRP CRP Polyamide 6.6			Shear strength according to DIN 53281 at:
Stainless Steel PC PMMA ABS Hard-PVC GRP Polyamide 6.6	20 N/mm ²		Aluminium
PC PMMA ABS Hard-PVC GRP CRP Polyamide 6.6	23 N/mm ²		Steel sand blasted
PMMA ABS Hard-PVC GRP CRP Polyamide 6.6	22 N/mm ²		Stainless Steel
ABS Hard-PVC GRP CRP Polyamide 6.6	12 N/mm ²		°C
Hard-PVC GRP CRP Polyamide 6.6	9 N/mm ²		PMMA
GRP CRP Polyamide 6.6	7 N/mm ²		ABS
CRP Polyamide 6.6	12 N/mm ²		Hard-PVC
Polyamide 6.6	21 N/mm ²		GRP
	22 N/mm ²		CRP
Townshing and interest	1 N/mm ²		^o olyamide 6.6
iemperature resistance -55 1	5 to +125 °C	-5	Temperature resistance

Surface pre-treatment

The prerequisite for perfect adhesion are clean and dry surfaces (e.g. cleaning and degreasing with WEICON Surface Cleaner). The highest strength values can be achieved through additional pre-treatment of the surfaces, such as roughening using blasting or abrasive agents. Several plastics, in particular polyamide, Teflon®, polyolefin etc. can only to be bonded after special surface treatment, for example using fluoridation, low-pressure plasma, corona, flame impingement etc.

Processing

WEICON Easy-Mix products can be processed directly from the double cartridges with the help of the included static mixer. Reject the first 5 cm of the dosed bead. Apply adhesive to only one of the surfaces to be bonded. The pot life given is for a material quantity of 10 ml at room temperature. If larger quantities are used, the curing time will be faster. Similarly, higher ambient temperatures shorten the cure times (as a rule of thumb, every +10°C increase above room temperature will halve working and curing time). Temperatures below +16°C will extend working and curing times considerably, while below about +5°C, no reaction will take place at all.

Storage

The shelf life is 12 months when stored unopened at a normal climate (+23 $^{\circ}$ C and 50 % rel. humidity).

Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience, since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON GmbH & Co. KG (Headquarters) Germany phone +49 (0) 251 9322 0 info@weicon.de

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05 info@weicon.ae

WEICON South East Asia Pte Ltd Singapore phone (+65) 6710 7671 info@weicon.com.sg WEICON Inc. Canada phone +1 877 620 8889 info@weicon.ca www.weicon.ca

WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013 info@weiconcz.cz WEICON Kimya Sanayi Tic. Ltd. Şti Turkey phone +90 (0) 212 465 33 65 info@weicon.com.tr www.weicon.com.tr WEICON Romania SRL Romania phone +40 (0) 3 65 730 763 office@weicon.com

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 info@weicon.es

Technical Datasheet

Create Date: 17.11.2017 - Seite 2/2

Available sizes:

10566050	Easy-Mix RK-7100 Structural Acrylic Adhesive 50 ml
Accessories:	
10650005	Mixing Nozzles Easy-Mix, Quadro
10653050	Dispenser D 50,
11202400	Sealant and Adhesive Remover, 400 ml
11207400	Surface Cleaner, 400 ml

- 11850200 Hand Protective Foam, 200 ml
- 12955175 Dosing Tips, Typ A Size 0,5

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON GmbH & Co. KG (Headquarters) Germany phone +49 (0) 251 9322 0 info@weicon.de

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05 info@weicon.ae

WEICON South East Asia Pte Ltd Singapore phone (+65) 6710 7671 info@weicon.com.sg

WEICON Inc. Canada phone +1 877 620 8889 info@weicon.ca www.weicon.ca

WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013 info@weiconcz.cz

WEICON Kimya Sanayi Tic. Ltd. Şti. phone +90 (0) 212 465 33 65 info@weicon.com.tr www.weicon.com.tr

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 info@weicon.es WEICON Romania SRL

Romania phone +40 (0) 3 65 730 763 office@weicon.com

R

Π

F

П

С