

Adhesive Spray DT



Allows Repositioning

Adhesive Spray DT for detachable joints is especially suited for non-permanent applications. It is colourless, does not soak through or cause discolouration, and does not leave a wavy surface, even when used on thin materials.

It can be used to bond paper, cardboard and foils to themselves and among each other. The joint is detachable when the spray is applied to one side; applying the spray to both sides makes the joint permanent.

It can be used, for example, to fuse templates, billboards, posters, photos, decorations in trade show construction, layouts and technical drawings.

Technical Data

Base	synthetic rubber
Processing temperature	(+50°F) +10 to (+86°F) +30 °C
Evaporation time	5 - 15 min.
open time max.	45 min.
Effectiveness	13 m ²
Temperature resistance	(-4°F) -20 to (+149°F) +65 °C
Storage stability	12 months

Processing

1. Shake can before use. Surfaces must be dry, clean and free of grease. Spray onto the surface at about 15 to 30 cm distance. Detachable if a thin adhesive layer is applied on only one surface. For permanent adhesion, Adhesive Spray should be applied either in a thick layer or on both surfaces. 2. Depending on surface characteristics and ambient temperature, let the spray film dry (about 10 minutes) until the adhesive is no longer stringy. 3. Position the parts and join them with strong pressur

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON GmbH & Co. KG
(Headquarters)
Germany
phone +49 (0) 251 9322 0
info@weicon.de
www.weicon.de

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae
www.weicon.ae

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca
www.weicon.ca

WEICON Kimya Sanayi Tic. Ltd. Şti.
Turkey
phone +90 (0) 212 465 33 65
info@weicon.com.tr
www.weicon.com.tr

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com
www.weicon.com.ro

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za
www.weicon.co.za

WEICON South East Asia Pte Ltd
Singapore
phone (+65) 6710 7671
info@weicon.com.sg
www.weicon.com.sg

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz
www.weicon.cz

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es
www.weicon.es

WEICON Italia S.r.l.
Italy
phone (+39) 0102924871
info@weicon.it
www.weicon.it